T CRAFT AERO CLUB CESSNA 182 N121M CHECK OUT SUPPLEMENT (Rev 5.6.24)

Name	Date	
CFI		
Total Flight Time for this checkout_discretion of the check-out CFI. Thi checkout if not currently checked ou Total Landings 4 Minimum (12)	s is an add t in the oth	lition to the normal C182 ner club C182's.

Prior to checkout: Read the POH, Checklist, Robinson STOL STC, and fill out a data sheet. Avionics documents on the club website/fleet page. Prior to check out you must get the Garmin Avionics training and get signed off on the G3X Checkout Checklist.

1. **Ground Phase - Review**

Certificates and Documents

Review Pilot Operating Handbook, Avionics, Robertson STOL STC, checklist, signed off on the G3X Checklist.

Interior Familiarization. Avionics, Controls, Autopilot, Pilot seat lock, Rear Seat adjustment/removal, tie-down.

Pilot Yoke: Electric Trim Control, Autopilot disengage, PPT.

Powerplant and Manifold Pressure Gauges, Leaning- Lean Assist

Constant Speed Propeller Operation

Flaps – Operate in each position and note how the Alerions follow flap extension. Maximum alerion droop at 20° Flap extension Note Larger Tires and Tow Bar Precautions

Weight and Balance (min and max weight, note CG differences)

2. Flight Phase

I	Pre Flight Inspection							
Engine Start, Taxiing, Before Take-off checklist								
Leaning on the ground								
Normal Take-off and Climb - No Flaps								
Normal Approach and Landing – Flaps as desired								
Vx Demonstration – Climb Rate Power On Stall								
Vy Demonstration – Climb Rate								
Performance Test Altitude Weight OAT BP								
Prior to test, disengage the ESP (Electronic Stability and Protection System) – You need								
to know how to do this.								
Slow Flight/Stall Test: Determine the power to maintain MCA (Minimum Control								
Airspeed) in level flight. – Stall Horn Just Starting to sound. Reduce Power while								
maintain altitude until Stall. Record IAS for each configuration. Note Angle of Attack								
tones an	d operation.							
Flaps	IAS @	IAS @	Margin	PWR	Notes			
1.00	MCA	Vs	MCA-Vs	MP/RPM	Notes			
0				/				
0				Pwr Off				
20				/				
20				Pwr Off				
40				/				
40				Pwr Off				
0				Pwr Off	20° bank			
0				Pwr Off	45° bank			
20				Pwr Off	20° bank			
20				Pwr Off	45° bank			
Leaning at Altitude								
S	Steep Turns							
F	Emergency Procedures – Simulated Engine Out, Best Glide							
Descent/Let Down Planning, Shock Cooling Avoidance								
Short Field Approach and Landing - 40° Flaps (if conditions permit)								
Short Field Take-off and Climb - 20° Flaps								
Soft Field Approach and Landing								
Soft Field Take-off and Climb - 20° Flaps								
	Cross Wind Operation (Take off and Landing) If possible							
	Go-Arounc	-	Ton (Tune	on and Eand	mg) ii possioie			
1 10105								
Signed								
_					Date:			
Member					Date:			